

**PCT**WORLD INTELLECTUAL  
Property Organization  
Internation

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)



WO 9603894A1

(51) International Patent Classification<sup>6</sup> :

A23L 1/226, A32G 3/30

A1

(21) International Application Number: PCT/US95/09903

(22) International Filing Date: 4 August 1995 (04.08.95)

(30) Priority Data:

08/286,286

5 August 1994 (05.08.94)

US

(71) Applicant: FUISZ TECHNOLOGIES LTD. [US/US]; Suite 100, 3810 Concorde Parkway, Chantilly, VA 22021 (US).

(71)(72) Applicants and Inventors: CHERUKURI, Subraman, R. [US/US]; 10 Jean Drive, Towaco, NJ 07082 (US). BATTIST, Gerald, E. [US/US]; 1588 N. Village Road, Reston, VA 22094 (US). ZAMUDIO-TENA, Jose, F. [US/US]; 2459 Glengyle Drive, Courtyard III, Vienna, VA 22181 (US).

(74) Agent: BARON, Ronald, J.; Hoffmann &amp; Baron, 350 Jericho Turnpike, Jericho, NY 11753 (US).

(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).

Published

With international search report.

(54) Title: COMESTIBLES CONTAINING STABILIZED HIGHLY ODOROUS FLAVOR COMPONENT DELIVERY SYSTEMS

(57) Abstract

Solid delivery systems for highly volatile flavor oils which include a stabilized, substantially non-volatile mixture of a highly volatile flavor oil or flavor component and a medium chain triglyceride are disclosed. The stabilized mixtures may be absorbed or adsorbed onto a non-fat solid substrate and incorporated into a saccharide based matrix and flash flow processed. The delivery systems may be added to chewing gum and confectionery products, as well as other pharmaceutical and comestible preparations.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

**COMESTIBLES CONTAINING STABILIZED HIGHLY ODOROUS  
FLAVOR COMPONENT DELIVERY SYSTEMS**

**FIELD OF THE INVENTION**

This invention relates to solid delivery systems for highly volatile flavor components and flavor oils for use in comestibles, such as gum and confectionery products, baked goods and other ingestible products. In particular, the present invention provides a means of making a stabilized, highly volatile flavor component-containing matrix for use in a variety of product applications.

**BACKGROUND OF THE INVENTION**

Many comestible products contain flavor oils and/or flavor components to provide the product with the desired taste and aroma, and to enhance the products' overall flavor perception in the mouth. Most flavors used in commercial applications are a complex mixture of compounds which have a particular taste and/or aroma associated with them. This generally holds true with respect to both natural and synthetic flavors and flavor components.

The volatility of flavor oils varies greatly, depending on the vapor pressures of the flavor components. Some of the more popular flavors, such as spearmint, peppermint, lemon, lime and cinnamon as well as numerous flavor components or compounds, such as menthol, benzaldehyde and camphor, are comprised of components which are extremely volatile, making them difficult to handle in manufacturing operations, as well as difficult to stabilize once they are incorporated into a product. For example, in the manufacture of chewing gum compositions and hard candies, volatile oils are generally one of the last ingredients to be added. This is because these confectionery compositions require mixing of the ingredients at temperatures which will quickly drive off the volatile components in the flavor

oils. In cases where the flavor oils are particularly volatile, i.e., evaporate quickly at room temperature, such manufacturing processes merely add to the complexity of capturing all the flavor components in a given flavor oil. Certain flavor components and flavor oils are so highly volatile that they are very difficult to handle and give off intense odors. The loss of certain flavor components, i.e., the more volatile compounds in the flavor oil, results in a flavor perception which is otherwise altered from its intended taste and aroma characteristics. Thus, to capture the true characteristics of a particular flavor oil, it is necessary to substantially minimize or effectively eliminate the loss of these components.

Simple mixing procedures have proved to be ineffective in maintaining all the flavor components in the mixture. Additionally, spray drying procedures have proved impractical because very little flavor was retained in the dried product. This is due in part to the heat and air exposure involved in the process. Furthermore, conventional spray drying or spray congealing processes require the feed material to sit for relatively long periods, i.e. hours, in the liquid state while they are waiting to be pumped into the feedlines and subsequently sprayed. This waiting period creates a heat history which is deleterious to heat sensitive materials which may be present in the feed material, e.g. volatile flavor oils, heat sensitive sweeteners and pharmaceuticals. Furthermore, the conventional processes require dispersing agents to keep components in the molten mixture from settling out prior to and during pumping to the nozzle. More recently, however, it has been discovered that flavor oils can be flash flow processed using flash heat or flash shear methods. Flash flow processing is described in U.S. Serial No. 08/205,026, filed March 2, 1994; U.S. Serial No.

08/081,338, filed June 29, 1993; and U.S. Serial No.  
07/847,595, filed March 5, 1992, commonly assigned to  
Fuisz Technologies, Inc., describes a method of providing  
a micronized oleaginous droplet in a saccharide-based  
5 matrix. Although flash flow processing has been found to  
be extremely effective in capturing the majority of  
flavor components during processing and protecting these  
components in the resultant matrices formed by the  
process, there is still a need to improve methods which  
10 prevent those especially high volatile components of the  
flavor oil from being lost.

It is apparent that there is a need for a method of  
handling and processing extremely volatile flavor oils  
and flavor components, as well as a product which  
15 maintains and delivers these materials without flavor  
loss.

#### SUMMARY OF THE INVENTION

The present invention is concerned with solid  
delivery systems for highly volatile flavor oils which  
20 include a stabilized, substantially non-volatile mixture  
of a highly volatile flavor oil or flavor component and a  
medium chain triglyceride. This mixture exhibits a  
substantially reduced vapor pressure and hence very  
little odor or volatility, notwithstanding the presence  
25 of highly volatile components. The incorporation of  
certain medium chain triglycerides in a mixture  
containing these oils is believed to be responsible for  
the stabilized, substantially non-volatile character of  
the mixture. This stabilized mixture allows for ease of  
30 handling of the highly volatile materials and facilitates  
the incorporation of these materials into a solid  
delivery system.

In addition, the medium chain triglyceride does not interfere with the taste or smell of a flavor as compared to many other oils, such as higher molecular weight triglycerides or fats, which contribute an adverse or undesirable taste component to the flavor system.

The stabilized, substantially non-volatile mixtures are combined with a saccharide-based matrix for use in comestibles, and preferably in chewing gum and confectionery products. In a preferred embodiment, the combination of the saccharide-based matrix and the stabilized, substantially non-volatile mixture is flash-flow processed to form a solid matrix having the stabilized, substantially non-volatile mixture united with the flash-flow-formed matrix. The stabilized, substantially non-volatile mixture of a highly volatile flavor component and medium chain triglyceride is a liquid. When combined with a solid saccharide-based material and subjected to flash flow processing, the resultant flash-flow-formed product is a solid saccharide-based matrix incorporating the liquid within the matrix. The resultant solid flash-flow-formed matrix further protects the highly volatile flavor oil and flavor oil components from volatilization. The combination of the stabilized mixture of medium chain triglycerides and highly volatile flavor oil and the flash flow process allows for incorporation of a higher amount of flavor oil in the final solid delivery system (flash-flow-formed matrix). Additionally, the final delivery systems have better flavor retention over time, i.e. less flavor loss due to the protective matrix, as well as a more uniform and consistent delivery of the flavor when incorporated into chewing gums, lozenges, hard candies and the like.

In another embodiment, the stabilized, substantially non-volatile mixture is absorbed or adsorbed onto a non-fat solid substrate. The substrate carries the stabilized mixture for use in food products, alone or in combination, with a flash flowable carrier material, such as a saccharide-based material. In such instances, the non-fat substrate having the stabilized, substantially non-volatile mixture absorbed/adsorbed thereon is added to a saccharide-based material and subjected to conditions of flash heat or flash shear.

In one particular embodiment, the stabilized, substantially non-volatile mixture is combined with a saccharide-based material and added directly to a chewing gum composition. In a more preferred embodiment of such products, prior to incorporation of this combination into the chewing gum composition, the stabilized flavor mixture/saccharide is subjected to flash flow processing. The resultant flash-flow-formed matrix is then incorporated into the chewing gum composition. In another embodiment of such products, the stabilized, substantially non-volatile mixture is absorbed/adsorbed onto a non-fat substrate and the resultant material is added to a saccharide-based matrix and either incorporated directly into the chewing gum composition or, in a preferred embodiment, subjected to flash flow processing prior to incorporation in the chewing gum product.

In another embodiment, the stabilized, substantially non-volatile mixture is added to a confectionery product such as a boiled candy. The stabilized mixture can be flash flow processed along with a saccharide-based material prior to incorporation into the candy or, as described above, absorbed or adsorbed onto a non-fat substrate prior to flash flow processing, and subsequently added to the candy composition.

5           The present invention also includes methods of stabilizing highly volatile flavor oils and flavor components by providing a mixture of these flavor oils and/or components and a medium chain triglyceride. This mixture is then combined with a saccharide-based material and either incorporated directly in a comestible product or subjected to flash flow processing prior to such incorporation.

10           In another embodiment of the present invention, the delivery systems are further combined with a fat material and flash flow processed to produce a solloid. Solloids are produced by methods described in copending U.S. Serial No. \_\_\_\_\_, filed July 1, 1994, (Docket 447-87/89) the application being incorporated herein by  
15           reference. The production of solloids further enhances the protection and stabilization of the highly volatile oils and/or flavor components and, as described in the aforementioned application, allows for uniformity of distribution of the oils in each solloid.

20           The resultant solid, particulate flavor delivery system can be added to a chewing gum composition, confectionery product, oral hygiene product, pharmaceutical product or other food or personal products which require flavoring.

25           The term "flash flow" has become recognized in the art as referring the conditions of temperature and force required to transform a solid feedstock having a certain morphological and/or chemical structure to a new solid having a different morphological and/or chemical  
30           structure without subjecting the solids to heat history or other requirements inherent in extrusion processing. The term "flash flow" is described in co-owned U.S. Patents 5,236,734, issued August 17, 1993 and 5,238,696, issued August 24, 1993, as well as co-pending U.S.S.N.



07/787,245 filed November 4, 1991, U.S.S.N. 07/893,238, filed June 30, 1992, U.S.S.N. 07/847,595, filed March 5, 1992 and U.S.S.N. 099,200, filed July 29, 1993.

5       The term "flash flow" refers to subjecting an appropriate feedstock to conditions of temperature and force which induce a solid feedstock to undergo rapidly such physical and/or chemical transformation. The time during the feedstock material is subjected to temperatures is very short. Flash flow processing can be  
10       accomplished either by a flash heat method or a flash shear method, as described further herein. In the flash heat method, the material subjected to temperature for generally only tenths of a second, whereas in the flash shear method the material is subjected to temperatures  
15       for a time on the order of seconds.

      In the flash heat process, a shearform matrix can be formed by spinning a feedstock in a "cotton candy" fabricating type machine. The spinning machine used to achieve a flash heat process can be a cotton candy type  
20       machine, such as the EconoFloss Model 3017, manufactured by Gold Metal Products Company of Cincinnati, Ohio, a machine having a coiled heater element as disclosed in U.S.S.N. 954,257, filed September 30, 1992 (herein incorporated by reference) and the like. It will be  
25       appreciated by those skilled in the art that any apparatus or physical process which provides similar forces and temperature gradient conditions can also be used. For simplicity in disclosing and describing this invention, the term flash heat will be understood to mean  
30       a process which includes subjecting a feedstock to the combination of temperature, thermogradients, flow, flow rates and mechanical forces of the type produced in a candy machine or the above-referenced U.S.S.N. 964,257 application. The apparatus is operated at the  
35       temperature and speed which permits flash heat of the

feedstock with deterioration of any of its ingredients.

5 In the flash heat process, the feedstock material is heated sufficiently to create an internal flow condition, i.e., intraparticle flow, which permits part of the feedstock to move at a subparticle level with respect to the rest of the mass and exit openings provided in the perimeter of the spinning head. The centrifugal force created in the spinning head flings the flowing feedstock material outwardly from the head so that it reforms with a changed structure. The force required to discharge flowable feedstock is provided by the forces which result from the spinning head. The flash heat process has been used to produce an amorphous matrix from a crystalline material, as disclosed in the aforementioned Fuisz patents. In the present invention, the feedstock comprises a combination of the stabilized, substantially non-volatile mixture and a saccharide-based material. The stabilized, substantially non-volatile mixture may be absorbed or adsorbed onto a non-fat substrate prior to incorporation into the flash flowable material.

20 Alternatively, the non-fat solid substrate having the stabilized, substantially non-volatile mixture associated therewith may be further incorporated into a solid fat, which is then subjected to heat and force sufficient to permit intraparticle flow of the fat. In this embodiment, the centrifugal force flings the feedstock material undergoing intraparticle flow into the air where the frictional forces provided by the ambient air disrupt the stream of such material, and lock the new morphological structure of the newly formed masses in place. The resultant product is the spheroidal-shaped solid suspension, i.e., a solid suspended in a solid, referred to herein as a "solloid."

In the flash shear process, a shearform matrix is formed by raising the temperature of the feedstock material, which includes a non-solubilized component, to a point where said component undergoes intraparticle flow. The non-solubilized component is preferably a fat which is solid at about room temperature. The feedstock is advanced and ejected from an extruder or similar type of machinery while the fat is undergoing intraparticle flow and is then subjected to disruptive fluid shear forces to form multiple parts or masses which comprise the individual spheroidal solloids.

The solloids are substantially cooled immediately after contact with the fluid shear force and are permitted to continue in a free-flow or free-fall condition, whereby they are further cooled to prevent individual solloids from adhering to each other and to maintain a free-flow condition. In addition to fats and other oleaginous materials, the feedstock material may also be a saccharide-based material or other flash shear processable materials.

It is important that the feedstock selected for the flash flow process have the ability to be processed without reliance upon dissolution. Furthermore, since highly volatile flavor oils and flavor components are present, it is important that these materials not be exposed to substantial heat for long periods of time. When fat-based materials are combined with the solid delivery system of the present invention, the feedstock is a solid material at room temperature, and is then subjected to the flash shear or flash heat process. No solvents or liquids are required in the present invention. The processes of the present invention are solid-to-solid processes which occur rapidly, with little or no heat history during processing.

The flash shear process can be carried out in an apparatus which has means for increasing the temperature of a non-solubilized feedstock and means for simultaneously advancing it for ejection. A multiple heating zone twin extruder can be used for increasing the temperature and advancing feedstock. The apparatus includes a means for ejecting the feedstock in a condition for shearing it to provide the shearform matrix. The means for ejecting is in fluid communication with the means for increasing the temperature and is arranged at the point to receive the feedstock while it is in the internal flow condition. The means for ejecting the feedstock is preferably a nozzle which provides sufficient frictional gas force applied to the ejected feedstock stream to disrupt the stream and form and maintain a solloid.

Apparatus for flash shear processing of the feedstock is described in co-pending U.S.S.N. 965,804, filed October 23, 1992. The means for shearing is arranged proximally to the ejector and is disposed to effect the shear of the feedstock while it is in the internal flow condition. Preferably, the means for shearing is the means for delivering fluid such as air at sufficient velocity and at elevated temperature against the feedstock stream as it exits a nozzle. Such a device can be an external atomizing nozzle. The means for shearing can also be a chamber in which the environment can be maintained to induce shear upon the collision of a high velocity of a stream of feedstock directed against a preselected and maintained environment.

#### DETAILED DESCRIPTION AND PREFERRED EMBODIMENT

It is known that food stimulates the sense of smell, taste and touch. The interpretation and characterization of this stimuli is subjective and involves the combination smell and taste sensations which are usually

expressed and described as flavor. The smell and taste functions are part of a complicated sensory ability which is stimulated by certain molecules. Compounds responsible for taste are predominantly part of the non-volatile portion of a flavor system which acts on the taste buds of the tongue or on the inner parts of the mouth. Compounds which are responsible for smell or odor are generally volatile molecules, which have been carried by the air stream into the upper nasal cavities where they trigger the neurons in the olfactory epithelium.

Typical verbal descriptors of odorous, i.e. volatile, compounds include expressions such as pleasant, flat, strong, sharp, mild and fresh as well as more precise expressions such as fruity, flowery, fatty, rancid, resinous, mouldy, and balsamic. Comparisons and associations are also commonly made. For example, flavors are also referred to as wax-like, nut-like, honey-like and so on. These verbal descriptions of the tonalities and characteristics represent the qualitative aspect of the odorous compounds. The qualitative aspect of a flavor is generally referred as its power, i.e., the threshold level at which a compound can be detected by sensory means, usually by 50% of an expert panel.

Of the total flavor sensation, many authorities believe that odor is more important than taste. For example, experience has shown that flavor sensation is markedly reduced when the nasal passages are partially blocked, such as in the case of a common cold. The flavor may be referred to as tasting flat in such cases. In actuality, the taste buds are functioning but the odor component of the flavor is not perceived.

The odor component of flavor is made up of at least two vectors. One vector is called the absolute external odor or fundamental odor of a substance. This vector

involves the perception, i.e., sniffing of a substance without contact with the tongue. That is, molecular vapors or gases of the flavor oil or flavor component pass directly to the olfactory sensory in the nasal passages. This vector is dependent upon the vapor pressure, i.e., volatility of the flavor oil or flavor oil component.

The other vector is often referred to by researchers as the internal odor, because the molecules reach the olfactory sensors by way of the pharynx, a flattened tubular passage that connects the back of the mouth with the nasal cavities. Additionally, in the mouth, food which contains flavor components is also combined with saliva, altering not only the vapor pressure of the flavorings present, but sometimes exposing more and different flavorings, thereby affecting the flavor intensity and quality.

It is known that extremely dry substances exhibit very little flavor and tend to be odorless. For example, the odor of metallic substances are often difficult to detect. Generally, however, the addition of small amounts of moisture to a product containing a flavor oil or flavor component increases their fundamental odor by increasing vapor pressure and activating the flavoring substances present. In the case of highly volatile flavor oils and flavor components, this in fact is even more dramatic. Thus, it is important to preserve as much of the true character of a particular flavor oil and/or flavor component by capturing and preserving substantially all of the volatiles in the flavor such that it can be delivered effectively in a comestible. Certain flavor oils are known to be extremely harsh or have bitter tones or notes. Additionally, certain flavors impart an extremely tense perception with very small amounts. In such cases, it is preferred to deliver

small quantities of these oils. As previously mentioned, due to the high volatility of these oils, it is difficult to ensure that the proper quantities of oil are effectively transferred and maintained in the final comestible product. To compensate for this uncertainty, larger amounts of these oils are often incorporated during the manufacturing process to allow for normal vapor loss.

The present invention solves the difficulties in handling, manufacturing and maintaining comestible products which contain highly volatile oils. To achieve this goal, the present invention lowers the vapor pressure of highly volatile oils by combining them with a medium chain triglyceride to form a stabilized mixture. This mixture is substantially stable, has little or no aroma or odor, indicating that the volatility, i.e., vapor pressure, of the flavor oil and/or flavor oil component is substantially reduced. The stabilized mixture is then combined with a non-fat substrate and saccharide-based matrix and flash flow processed to yield a stable delivery system.

There are literally thousands of compounds which exhibit aromas. Flavors are generally composed of numerous compounds, each imparting a particular odor and taste. Natural flavorings usually come from a number of plant sources, such as bushes, herbs, shrubs, trees, weeds and specific parts of these substances. For example, arils, balsams, barks, beans, berries, blossoms, branches, buds, bulbs, calyxes, capsules, catkins, cones, exudates, flowering tops, flowers, fronds, fruits, gums, hips, husks, juices, kernels, leaves, needles, nuts, oils, oleoresins, peels, pits, pulps, resins, rhizomes, rinds, roots, seeds, shoots, stalks, stigmas, stolons, thallus, twigs, wood and wood sawdust, as well as entire plants, are examples of plant parts from which extracts

are taken to use for or as flavors.

In addition to plant sources, some fundamental flavoring substances are also obtained from animal sources. These are relatively few, however. Musk deer is one such flavoring substance which is obtained from the secretion of the male deer of the Himalayan highlands. Bees wax, a cured yellow wax is often used to enhance the flavor and textural qualities of honey. Bees wax is also used in perfumery. It is known that there is a close link between the technology of flavorings for the food field and fragrances used in perfumes, cosmetics and related products.

For purposes of the present invention, highly volatile or odorous flavor oils and flavor components will mean those oils, components and compounds which alone or in admixture have a vapor pressure of at least 40 mm at temperatures of up to 160°C and preferably having a vapor pressure of at least 40 mm at temperatures up to about 130°C. A partial listing of such highly volatile, odorous flavors and flavoring components includes:



	<u>Flavor/Flavor Component</u>	<u>Temperature Required To Achieve 40 mm Vapor Pressure</u>
	Methyl Acetate	- 7.9
	Ethyl Acetate	9.1
5	1-Hexanol	83.7
	Benzaldehyde	90.1
	Benzyl Alcohol	119.8
	1-Octanol	115.2
	2-Octanol	98
10	Cinnamaldehyde	152.2
	Cinnamyl Alcohol	151
	Naphthalene	140.1
	p-Cymene	87
	Thymol	139.8
15	Camphene	75.7
	d-Limonene	84.3
	Myrcene	82.6
	$\alpha$ -Pinene	90.1
	$\beta$ -Pinene	71.5
20	Terpenoline	100
	Camphor	114
	1-Dihydrocarvone	123.7
	$\alpha$ -Citral	135.9
	d-Fenchone	99.5
25	Pulegone	121.7
	$\alpha$ -Thujone	110
	d-Citronellal	116.1
	Cineol	84.2
	Dihydrocarveol	136.1
30	d,l-Fenchyl alcohol	110.8
	Geraniol	141.8
	d-Linalool	109.9
	$\alpha$ -Terpineol	126
	l-Menthol	126.1
35	d-Bornyl Acetate	123.7
	Goranyl Acetate	150
	Linalyl Acetate	127.7

The following flavor oils are known to be comprised of at least these components:

	Lime Oil:	$\alpha$ -P-Pinene, Camphene, $\beta$ -Pinene, Myrcene, $\alpha$ -Phellandrene
5	Spearmint Oil:	$\alpha$ -Pinene, $\beta$ -Pinene, Thujan-4-ol, Myrcene, $\alpha$ -Terpinene
	Lemon Oil:	$\alpha$ -Thujene, $\alpha$ -Pinene, Camphene, Thujan-4-ol, $\beta$ -Pinene
10	Cinnamon Oil:	Benzaldehyde, $\beta$ -Pinene, Cinnamaldehyde, Cinnamyl Alcohol
	Peppermint Oil:	$\alpha$ -Pinene, $\beta$ -Pinene, Thujan 4-ol, Myrcene, $\alpha$ -Terpinene

Other flavor oils which may be useful in the present invention may be selected from a wide variety of natural or artificial oils or essences. These oils are generally derived from plant extracts, although they may alternatively be synthetically derived. Peppermint oil, spearmint oil, cinnamon oil, oil of wintergreen, menthol, citrus oils and other fruit essences are the most commonly used flavor oils which are employed in the present invention. The solid delivery system of the present invention give the perception that a greater quantity of flavor is present than the actual amount, thereby enhancing both the organoleptic impact with less flavor oil and eliminating the need for higher amounts of flavor oil or active. This is particularly useful in applications such as chewing gum compositions, where the addition of flavor oil at high concentrations to achieve a more intense flavor impact results in plasticization of the gum base components and sloppy chew characteristics. Additionally, flavor oils such as peppermint oil, spearmint oil, menthol and cinnamon oil are particularly harsh and create a burning sensation in the mouth if ingested in too high a quantity. The present invention

allows for the use of smaller quantities than in typically comestible applications if desired, with the perception that greater quantities are present.

Alternatively, because the process allows for precision in the amount of active in the delivery system, higher loading of the active than in prior methods is possible. In essence, the processes of the present invention allow for precise control of the quantity of active in the delivery system.

Examples of citrus or fruit oils and/or essences which are useful include a host of materials such as apple, apricot, banana, blueberry, cherry, grape, grapefruit, lemon, lime, orange, pear, peaches, pineapple, plum, raspberry, strawberry and the like. Mixtures and derivatives of these materials are contemplated.

Additional flavoring agents may be chosen from synthetic flavor oils and flavoring aromatics, and/or oils, oleo resins and extracts derived from plants, leaves, flowers, fruits and so forth, and combinations thereof. For example, clove oil, bay oil, anise oil, eucalyptus oil, thyme oil, cedar leaf oil, oil of nutmeg, oil of sage, oil of bitter almonds and cassia oil may be used. Commonly used flavors include menthol, artificial vanilla, cinnamon derivatives, and various fruit flavors, whether employed individually or in admixture.

Flavorings such as aldehydes and esters including cinnamyl acetate, cinnamaldehyde, citral diethylacetal, dihydrocarvyl acetate, eugenyl formate, p-methylamisol, and so forth may also be used.

Further examples of aldehyde flavorings include, but are not limited to acetaldehyde (apple); benzaldehyde

(cherry, almond), anisic aldehyde (licorice, anise);  
cinnamic aldehyde (cinnamon); citral, i.e., alpha citral  
(lemon, lime); neral, i.e. beta citral (lemon, lime);  
decanal (orange, lemon); ethyl vanillin (vanilla, cream);  
5 hellotropine, i.e., piperonal (vanilla, cream); vanillin  
(vanilla, cream); alpha-amyl cinnamaldehyde (spicy fruity  
flavors); butyraldehyde (butter, cheese); valcraldehyde  
(butter, cheese); citronellal; decannal (citrus fruits);  
aldehyde C-8 (citrus fruits); aldehyde C-9 (citrus  
10 fruits); aldehyde C-12 (citrus fruits); 2-  
ethylbutyraldehyde (berry fruits); hexenal, i.e., trans-2  
(berry fruits); tolyl aldehyde (cherry, almond);  
veratraldehyde (vanilla); 2,6-dimethyl-5-heptenal, i.e.  
melonal (melon); 2,6-dimethyloctanal (green fruit); and  
15 2-dodecenal (citrus, mandarin), mixtures thereof and the  
like.

Other specific flavor compounds such as  
ethylacetate, thiophene, ethylpropionate, ethyl butyrate,  
2-hexanoate, 2-methylpyrazine, heptaldehyde, 2-octanone,  
20 limonene, and eugenol are also useful.

The flavor oil content of the present delivery  
systems is generally in the range of about 0.02% to about  
40% by weight of the delivery system. However,  
deviations from this range are certainly possible  
25 provided that the delivery system is formed using the  
flash flow process. Preferably, the oils are present in  
amounts of about 0.5% to about 30% by weight of the  
delivery system and most preferably about 2% to about  
12%.

30 As previously mentioned, the addition of the medium  
chain triglyceride to the highly volatile flavor oil or  
flavor component results in a mixture which is highly  
stabilized, i.e., the volatility is substantially reduced  
such that very little evaporation occurs at room

temperature. This is evident on a macro scale by the fact that little or not flavor odor is noticeable.

5 The stable, substantially non-volatile mixtures of the present invention, which include the medium chain triglyceride and the highly volatile flavor oil or flavor oil component, have a medium chain triglyceride content of about 0.1% to about 60%, and preferably 0.1% to about 20% by weight of the mixture. When present in these ranges, the medium chain triglyceride serves its valuable purpose as a vapor pressure lowering agent, which prevents premature and undesirable volatilization of highly volatile components.

10 The medium chain triglycerides of the present invention are selected from mono-, di- and polyhydric esters of a fatty acid, as well as mixtures thereof. Those fatty acids useful in forming the medium chain triglyceride have from 6 to 12 carbon atoms in the fatty acid chain. Non-limiting examples of fatty acids of this type are caprylic acid, capric acid, linoleic acid, caprioc acid, lauric acid, succinic acid and mixtures thereof. Preferably the medium chain triglyceride is the glycerol ester of these acids.

15 Specific examples of medium chain triglycerides useful in the present invention include those sold under the MIGLYOL® trademark by Hüls Aktiengesellschaft. There are various neutral, medium chain triglyceride oils marketed under the MIGLYOL® brand. For example: MYGLYOL® 810 is a medium chain triglyceride of fractionated C<sub>8</sub>-C<sub>10</sub> coconut oil fatty acids and is classified as a caprylic/capric triglyceride. It has a higher caprylic acid content and a correspondingly lower capric acid content than MIGLYOL® 812, which is also a caprylic/capric triglyceride. MIGLYOL® 818 is a triglyceride of fractionated C<sub>8</sub>-C<sub>10</sub> coconut oil fatty acids with a 5% portion of linoleic acid. It is

20  
25  
30  
35

classified as a caprylic/capric/linoleic triglyceride. MIGLYOL® 829 is a glyceryl ester of fractionated C<sub>8</sub>-C<sub>10</sub> coconut oil fatty acids linked to succinic acid. It is classified as a caprylic/capric/diglyceryl succinate triglyceride. MIGLYOL® 840 is a propylene glycol diester of saturated vegetable fatty acids with C<sub>8</sub>-C<sub>10</sub> chain-lengths and is classified as a propylene/glycol/dicaprylate/dicaprate triglyceride.

In addition to the MIGLYOL® brand of medium chain triglyceride oils, other brands such as NEOBEE® M-5, a caprylic/capric triglyceride from Stepan Company, Maywood, NJ, and DIGEST™ 65, a medium chain triglyceride prepared from edible vegetable oil and having a minimum of 65% C<sub>8</sub> esters present, and have been found to be useful.

As previously pointed out, medium chain triglycerides have been used as stable lipid solvents for colors, flavors, vitamins, antioxidants, and pharmaceuticals. These low viscosity oils have also been used in confectionery products as anti-sticking and lubricating agents and for dust prevention for spices, seasonings and other dry mixes.

The preferred medium chain triglycerides of the present invention include the fractionated C<sub>8</sub>-C<sub>10</sub> coconut oil fatty acids classified as caprylic/capric triglycerides.

As a preferred embodiment, the stabilized medium chain triglyceride/highly volatile flavor oil mixture is combined, absorbed or adsorbed onto a non-fat solid substrate. For purposes of this invention, the term "non-fat" solid substrate will mean materials which are generally not considered fats in themselves and which are capable of absorbing, i.e. imbibing, or adsorbing the

flavor oils. For example, such materials include, without limitation, cellulosics, silicas, microcrystalline waxes, water-swellaable gums, water-swellaable mucilages, alginates, carageenans, tragacanth, starches, calcium and magnesium carbonate, titanium dioxide, zein and mixtures thereof.

The aforementioned mixtures may be imbibed by or adsorbed onto the non-fat solid substrate either by soaking, mixing or coating the substrate with the mixture of medium chain triglyceride and highly volatile flavor oil. The non-fat solid substrate further protects potential volatilization during the flash flow process. As previously mentioned, however, since the flash flow process has substantially little heat history and occurs extremely quickly, volatilization during the process is already substantially reduced over conventional food processing.

The non-fat solid substrates may be selected from a wide variety of materials. One limitation, however, is that the melting point of the material chosen for the non-fat solid substrate must be such that, if flash flow process is used, the non-fat solid does not melt during the flash flow process. This means that the melting point of the non-fat solid substrate must be beyond the flow point temperature of the solid fat. In cases where flash flow processing is not used, this limitation does not, however, apply.

Representative non-fat solid substrates include, without limitation, those materials which are adsorbent as well as absorbent. For example, cellulosic materials such as alkyl celluloses, hydroxyalkyl celluloses and hydroxyalkylalkyl celluloses are contemplated. These include methylcellulose, hydroxymethyl cellulose, hydroxyethyl cellulose, hydroxypropyl cellulose,

hydroxyethylmethyl cellulose, hydroxypropylmethyl cellulose, hydroxybutylmethyl cellulose, cellulose esters and hydroxyalkyl cellulose esters. Cellulose acetylphthalate and hydroxypropylmethyl cellulose are among those useful. Additionally, carboxyalkyl celluloses and their esters, as well as carboxyalkylalkyl celluloses and their esters are also useful. One example is carboxymethyl cellulose.

Other non-fat solid substrates include water swellable gums and mucilages, algal polysaccharides, pectin and lignin. For example, karaya gum, acacia gum, tragacanth, sodium alginate, calcium alginate, carageenan and its salts, as well as mixtures thereof may be employed. Starches, including chemically and biologically modified starches are also contemplated as being useful. Calcium carbonate, magnesium carbonate and stearate and the like are also useful. Additionally, protein materials such as zein, sorghum and other prolamines may also be employed.

Various silicas and microcrystalline substances are also useful as the solid non-fat substrate. For example, silicas are well known for their ability to absorb or otherwise capture liquids and certain silicas are extremely porous in nature. For example, synthetic amorphous silica has been particularly useful since it has a unique combination of uniformity, chemical inertness, large surface area and porosity which makes it very adsorptive. These silicas are manufactured with precisely controlled surface area, porosity and particle size distribution. This makes them particularly useful in the inventive compositions. Commercially available silicas of this kind are sold under the trademarks SYLOID® and SYLOX® by W.R. Grace & Company, Baltimore, Maryland. These materials are specifically intended for conventional liquid dispersions and suspensions.



However, they are also useful in the delivery systems of the present invention.

It is preferred that the non-fat solid substrate have muco-adhesive properties. This means that the substrate has an affinity for adhering to the mucosal membranes of the body, particularly in the mouth, such that the active can be either absorbed quickly or in the case of flavorants, perceived for long periods of time in the oral-cavity, since the active agents are carried by the substrate. These substrate materials adhere when subjected to the moist conditions of the mouth, largely because of their physical and chemical affinity to the mucosal membrane structure. The carboxyl and hydroxyl hydrophilic groups on the substrates, as well as other hydrophilic groups which may be present, are believed to be largely responsible for the affinity and adhesion of these classes of materials to the mucosal membrane. These materials also have the capability of being smooth and devoid of any unpleasant texture in the mouth. For this reason, their lubricous mouth-feel allows for them to be virtually imperceptible when bound to the mucosal surface, thereby allowing the active to be slowly released in the mouth, in the case of flavorants, or in the bloodstream in the case of drugs or medicaments which may also be included in the delivery systems of the present invention.

The preferred non-fat solid substrate of the present invention is hydroxypropylmethyl cellulose. This particular substrate has found to be especially useful in chewing gum compositions and other confectionery products.

One advantage of the present invention is that the highly volatile flavor or flavor component is in substantially the same proportion in the delivery system

as it is in the stabilized mixture of medium chain triglyceride/flavor oil. This is particularly useful in dosage forms where the active content is critical.

5 Final dosage forms in which the delivery system may be present can be selected from any number of vehicles or dosage forms. For example, food products, medicaments, baked goods, pharmaceutical preparations, lozenges, capsules, nuggets, dentifrices, liquids and gels may be employed among others. When incorporated into chewing  
10 gum and confectionery compositions, the delivery systems are present in amounts of about 0.05% to about 30% by weight, and preferably about 0.1% to about 20% by weight of the total compositions. Other products may contain the delivery system in effective amounts required to  
15 perceive the desired effect. In the case where medicaments having adverse tastes are incorporated with the stable mixture, the flavors may be present in an amount such that the adverse taste is ameliorated.

20 Once prepared, the delivery systems may be stored for future use or formulated with conventional additives such as pharmaceutically acceptable carriers and confectionery ingredients to prepare compositions which offer a variety of textures to suit particular applications. Pharmaceutically acceptable carriers may  
25 be selected from a wide range of materials. Without being limited thereto, such materials include diluents, binders and adhesives, lubricants, disintegrants, colorants, flavorings, sweeteners and other miscellaneous materials such as buffers and adsorbents used to prepare  
30 a particular medicated composition. In addition, elixirs, and syrups whereby the colloids are suspended therein are also contemplated.

The present invention contemplates the inclusion of those sweeteners well known in the art, including both natural and artificial sweeteners. Thus, sweeteners may be chosen from the following non-limiting list; sugars  
5 such as sucrose, glucose (corn syrup), dextrose, invert sugar, fructose, and mixtures thereof; saccharin and its various salts such as the sodium or calcium salt; cyclamic acid and its various salts such as the sodium or calcium salt; the dipeptide sweeteners such as aspartame  
10 and alitame; chlorinated sugar derivatives such as sucralose; natural sweeteners such as dihydrochalcone; glycyrrhin; Stevia rebaudiana (Stevioside); and sugar alcohols such as sorbitol, sorbitol syrup, mannitol, xylitol, and the like. Also contemplated as a sweetener  
15 is the nonfermentable sugar substitute hydrogenated starch hydrolysate (lycasin) which is described in U.S. Patent No. Re. 26,959. Also contemplated is the synthetic sweetener 3,6-dihydro-6-methyl-1-1,2,3-oxathiazin-4-one-2, 2-dioxide particularly the potassium  
20 (Acesulfame-K), sodium and calcium salts thereof as described in German Patent No. 2,001,017.7.

The sweeteners may be incorporated as the active agent, per se, i.e., flash flow processed with the non-fat solid or substrate to form a substrate/active  
25 combined solid, combined with the stabilized medium chain triglyceride/flavor oil as the active or incorporated directly in the fat matrix.

The delivery system can be incorporated in conventional chewing gum compositions. These  
30 compositions typically contain a sweetener, a gum base and a flavor. Additionally sources of flavor and/or sweetener can of course be combined with the solloid delivery system and incorporated in the chewing gum composition.

In the present invention, the flavor, sweetener and optionally acidulants can be incorporated into the delivery system. For example, in one embodiment a flavorant selected from the group consisting of flavor oils, sweeteners, food acids (also referred to as acidulants), and mixtures thereof may be united with the solid non-fat substrate. Preferably a mixture of all three are present. In another embodiment, one or more of the flavorant materials may additionally be incorporated into the solid fat matrix such that it remains in the solid fat portion of the solloid.

Chewing gum compositions incorporating the novel delivery systems have distinct advantages in terms of sustained flavorant perception. Due to the physical structure of the delivery system, the flavorant materials are protected during processing as well as in the bulk storage form subsequent to processing. Once incorporated into a chewing gum composition, the delivery system serves to protect the flavorants from other components in the chewing gum as well as preventing migration of the flavorant from the gum base onto the surface of the gum.

One particular advantage to the inventive delivery systems relates to their ability to sustain the flavor and sweetness perception of the chewing gum. The non-fat solid substrate preferably has a muco-adhesive property which serves to adhere the solloids to the mucous membranes of the mouth. The solloids slowly release their flavorant materials through a delayed hydration process. The perception of flavor and sweetness is significantly increased due to the presence of the solloids in the mouth during mastication

With regard to chewing gum compositions, the amount of gum base employed will vary greatly depending on various factors such as the type of base, consistency

desired and other components used to make the final product. In general, amounts of about 5% to about 85% by weight of the final chewing gum compositions are acceptable, with amounts of about 15% to about 30% by weight being preferred. The gum base may be any water-insoluble gum base well known in the art. Illustrative examples of suitable polymers in gum bases include both natural and synthetic elastomers and rubbers. For example, those polymers which are suitable in gum bases include, without limitation, substances of vegetable origin such as chicle, jelutong, gutta percha and crown gum. Synthetic elastomers such as butadiene-styrene copolymers, isobutylene-isoprene copolymers, polyethylene, polyisobutylene, polyvinylacetate and mixtures thereof are particularly useful.

The gum base composition may contain elastomer solvents to aid in softening the rubber component. Such elastomer solvents may comprise methyl, glycerol or pentaerythritol esters of rosins or modified rosins, such as hydrogenated, dimerized or polymerized rosins or mixtures thereof. Examples of elastomer solvents suitable for use herein include the pentaerythritol ester of partially hydrogenated wood rosin, pentaerythritol ester of wood rosin, glycerol ester of wood rosin, glycerol ester of partially dimerized rosin, glycerol ester of polymerized rosin, glycerol ester of tall oil rosin, glycerol ester of wood rosin and partially hydrogenated wood rosin and partially hydrogenated methyl ester of rosin, such as polymers of alpha-pinene or beta-pinene; terpene resins including polyterpene and mixtures thereof. The solvent may be employed in an amount ranging from about 10% to about 75% and preferably about 45% to about 70% by weight of the gum base.

A variety of traditional ingredients such as plasticizers or softeners such as lanolin, stearic acid, sodium stearate, potassium stearate, glycerol triacetate, glycerin and the like, including, natural waxes, such as paraffin waxes and microcrystalline waxes may also be incorporated into the gum base to obtain a variety of desirable textures and consistency properties. In accordance with the invention, however, these ingredients may be reduced in amount or in some cases, may be eliminated entirely. When present, these individual additional materials are generally employed in amounts of up to about 15% by weight and preferably in amounts of from about 3% to about 10% by weight of the final gum base composition.

The chewing gum may additionally include the conventional additives of coloring agents such as titanium dioxide; emulsifiers such as lecithin and glycerol monostearate; additional fillers such as aluminum hydroxide, alumina, aluminum silicates; calcium carbonate, and talc and combinations thereof; and additional flavoring agents. These fillers may also be used in the gum base in various amounts. Preferably, the amount of fillers when used will vary from about 4% to about 35% by weight of the final chewing gum.

The amount of delivery system used in the chewing gum composition will largely be a matter of preference. It is contemplated that the delivery system will be included in amounts of from about 0.25% to about 40% by weight of the final gum composition, with amounts of from about 1% to about 30% being preferred, and amounts of from about 1% to about 20% being most preferred.

In addition to the inventive delivery system, the chewing gum composition may also optionally include one or more additional ingredients such as conventional

saccharide-based bulking agents including sugars or sugar alcohols, flavor delivery systems, spray-dried flavors, liquid flavors, natural and/or artificial sweeteners and the like.

5           The chewing gum compositions of the present invention may be prepared by combining the water-insoluble gum base portion and the water-soluble flavor portion including the novel flavor delivery system according to conventional chewing gum processing  
10 techniques.

For illustrative purposes, a method of preparing the novel chewing gum compositions is as follows:

A suitable chewing gum base is first melted. Softeners and bulking agents such as sugars or sugar  
15 alcohols if desired may be added slowly with stirring thereafter. The inventive delivery system is then added and mixing is continued until a homogeneous mass is achieved. Optionally, additional flavor oils or spray  
20 dried flavors may be added as well. The mass may then be rolled, scored, dusted and wrapped in any manner known in the art.

With regard to the preparation of other types of comestibles, the inventive delivery system may also be added in a conventional manner. For example, in the case  
25 of pressed tablets, the delivery system may be dry blended with the remaining tablet ingredients and the mixture thereafter compressed into final tablet form. In the case of dentifrices, denture creams and cleansers, the products also benefit from incorporation of the  
30 delivery system in their formulations. In short, the matrix may be added to various comestibles in a manner similar to that which the skilled artisan currently uses to add conventional comestible ingredients.

In one particular embodiment, a micron-sized synthetic, amorphous silica has been used as the non-fat solid substrate for liquid actives. Using these materials, the stabilized, flavor oil/medium chain triglyceride mixture can be adsorbed onto their surfaces and into their pores and the added to the feedstock of matrix material to form the inventive delivery systems. In this manner, additional controlled release characteristics can be imparted to the delivery systems, as well as adding further stabilization and protective features to the oils against volatilization and oxidation. These silica compounds also have ionic and hydrogen bond affinity for certain flavor component chemical groups, which affinity serves to strengthen flavor retention and consequently allows for increased delayed release capabilities and stabilization characteristics.

Additional materials which can be used as carriers for the flavor oils prior to incorporation with the inventive delivery system include maltodextrins, such as spray-dried maltodextrin marketed under the tradename M100 (10 DE) by Grain Processing Corporation, Muscatine, IA, as well as agglomerated maltodextrin (10 DE) sold under the tradename Micropor Buds 1015A, by E. Staley Manufacturing Co., Decatur, IL. These materials are also porous and allow for flavor retention. Polydextrose and microcrystalline cellulose are also useful in this regard, as are a number of other adsorbent materials.

#### EXAMPLES

The following examples serve to provide further appreciation of the invention, but are not meant in any way to restrict the effective scope of the invention.



EXAMPLE ONE

5 A stabilized substantially non-volatile mixture of  
15% by weight % a caprylic/capric triglyceride (MIGLYOL®  
810) and 10% by weight of the highly odorous, highly  
5 volatile flavor component benzaldehyde was made. This  
stabilized mixture was added to maltodextrin (MALTRIN® M-  
365, Grain Processing Corporation) and flash flow  
processed using an Econo Floss cotton candy machine. The  
temperature and spinning head speed were set at levels  
10 sufficient to produce a solid flash-flow-formed matrix  
containing benzaldehyde. Low temperatures are, of  
course, preferred. The resultant solid delivery system  
was in the form of white flakes with substantially very  
little benzaldehyde fumes or odor being observable by  
15 smell.

EXAMPLE TWO

20 A stabilized, substantially non-volatile and odor  
free mixture of diacetyl (5% by weight) and a medium  
chain triglyceride of fractionated C<sub>8</sub>-C<sub>10</sub> coconut oil  
fatty acids, i.e. caprylic/capric triglyceride, was made  
and added to maltodextrin (MALTRIN® M-365, 80% by  
weight). The combination was then added to an Econo  
Floss cotton candy machine and flash-flow-processed to  
form greenish yellow flakes which comprise the inventive  
25 delivery system. The delivery system was substantially  
odor free, indicating little or no volatilization of the  
flavor oil component.

EXAMPLE THREE

The following delivery system was prepared by incorporation into a chewing gum composition.

	<u>Delivery System A</u>	<u>% By Weight</u>
5	Medium chain triglyceride	7.5
	Non-fat solid substrate	
	(a) starch	10.0
	(b) hydroxypropylmethyl cellulose	16.0
	(c) calcium carbonate	10.0
10	Menthol crystals	7.50
	Flavor enhancer	0.15
	Sorbitol	6.00
	Emulsifier and other additives	8.0
	Polydextrose	<u>34.85</u>
15		100.00

The above ingredients were admixed and flash-flow-processed to form a solid stabilized high volatile-containing delivery system having little or no odor.

The resultant delivery system was added to the following chewing gum composition.

	<u>Chewing Gum Composition</u>	<u>% By Weight</u>
	Gum base	24.894
	Sweetener (sugar alcohol)*	57.310
	Lycasine	2.686
5	Calcium carbonate	6.268
	Emulsifier	0.304
	Glycerin	0.501
	Spearmint oil (free)	1.612
	Spearmint oil (spray dried)	1.003
10	Artificial Sweetener**	0.156
	Delivery System A	<u>2.006</u>
		100.000

\* xylitol and lactitol

\*\* aspartame and acesulfame-K

15           The chewing gum composition was prepared in  
accordance with the methods described herein. Chewing  
gum panels were conducted for sensory evaluation with  
respect to flavor intensity and flavor duration. The  
results of the panel demonstrated that chewing gum  
20       compositions using the delivery system of the present  
invention exhibited a continuum of uniform flavor  
throughout a period of 60 minutes or more. The chewing  
gum composition remained stable without observable loss  
of flavor volatiles or migration of the flavor oil from  
25       the delivery system into the remainder of the chewing gum  
composition.

#### EXAMPLE 4

A stabilized, substantially non-volatile mixture of  
15 grams of a medium chain triglyceride and 22.5 grams of

menthol crystals was formed. To this mixture was added .45 grams of F, D and C Blue No. 1 H.T. Lake. A second mixture comprising 22.5 grams of polyethylene glycol (8,000 carbowax) with 12 grams of hydrogenated cottonseed oil was heated separately. An additional mixture of 129.6 grams of corn sugar solids (maltodextrose M-365), 45 grams of hydroxypropylmethyl cellulose, 1.5 grams of lecithin, 15 grams of calcium carbonate, 0.4 grams of capsicum, 30 grams of xylitol and 6 grams of sorbitol was formed. The separate mixtures were then combined and placed in a spinning machine having a 7" cable heater head with a 0.030" gap between heating cables. The mixture was then flash flowed to produce a delivery system containing menthol flavor crystals.

The delivery system was then added to a candy matrix. The matrix was prepared by mixing 220 grams of corn syrup 43° Baume (Cargill), 330 grams of granulated sugar and 145 ml of water. The candy matrix was heated to 300°F, poured into a cooling pan and permitted to sit for 2-3 minutes to achieve a pliable state. The delivery system containing the menthol flavor crystals was then added and mixed into the candy matrix. The matrix was allowed to fully cool and was then cut into small pieces for consumption.

WHAT IS CLAIMED IS:

1. A chewing gum composition comprising:
  - (i) a gum base; and
  - (ii) a particulate flavor delivery system comprising a non-fat solid substrate having adsorbed thereon or  
5 absorbed therein a mixture comprising a highly odorous flavor oil component and a medium chain triglyceride.
2. The chewing gum composition of claim 1 wherein the medium chain triglyceride is selected from the group consisting of mono-, di- and polyhydric esters of a fatty acid and mixtures thereof.
3. The chewing gum composition of claim 2 wherein said medium chain triglyceride has from 6 to 12 carbon atoms in the fatty acid chain.
4. The chewing gum composition of claim 3 wherein the medium chain triglyceride is formed from a fatty acid selected from the group consisting of caprylic acid, capric acid, linoleic acid, caproic acid, lauric acid,  
5 succinic acid and mixtures thereof.
5. The chewing gum composition of claim 4 wherein the medium chain triglyceride is the glycerol ester of said acids.

6. The chewing gum composition of claim 1 wherein the highly odorous flavor oil component has a vapor pressure of at least about 40 mm at a temperature of about 160°C or less.

7. The chewing gum composition of claim 6 wherein the highly odorous flavor oil component is selected from the group consisting of methyl acetate, ethyl acetate, 1-hexanol, benzaldehyde, benzyl alcohol, 1-octanol, 2-octanol, cinnamaldehyde, cinnamyl alcohol, naphthalene, 5 p-cymene, thymol, camphene, d-limonene, myrcene,  $\alpha$ -pinene,  $\beta$ -pinene, terpenoline, camphor, 1-dihydrocarvone,  $\alpha$ -citral, d-fenchone, pulegone,  $\alpha$ -thujone, d-citronellal, cineol, dihydrocarveol, d,l-fenchyl alcohol, geraniol, d-10 linalool,  $\alpha$ -terpineol, 1-menthol, d-bornyl acetate, geranyl acetate, linalyl acetate, d and mixtures thereof.

8. The chewing gum composition of claim 7 wherein said flavor delivery system further comprises a flavor oil selected from the group consisting of peppermint oil, spearmint oil, eucalyptus oil, cinnamon oil, menthol, oil 5 of wintergreen (methylsalicylate), citrus oils, fruit essences and mixtures thereof.

9. The chewing gum composition of claim 1 wherein said non-fat solid substrate is a muco-adhesive.

10. The chewing gum composition of claim 9 wherein said muco-adhesive is selected from the group consisting of cellulosics, silicas, microcrystalline waxes, water-swella-  
5 ble gums, water-swella-ble mucilages, alginates, carageenans, tragacanth, starches, calcium carbonate, magnesium carbonate, titanium dioxide, zein and mixtures thereof.

11. The chewing gum composition of claim 1 wherein said non-fat solid substrate is hydroxypropylmethyl cellulose.

12. The chewing gum composition of claim 11 wherein said non-fat solid substrate additionally includes starch.

13. The chewing gum composition of claim 12 wherein said non-fat solid substrate additionally includes calcium carbonate.

14. The chewing gum composition of claim 1 wherein said flavor delivery system is present in amounts of about 0.05% to about 30% by weight of the chewing gum composition.

15. The chewing gum composition of claim 1 wherein said non-fat solid substrate is present in said delivery system in amounts of about 1% to about 40% by weight.

16. The chewing gum composition of claim 1 wherein said highly odorous flavor oil component is present in amounts of about 0.1% to about 30% by weight of said mixture.

17. The chewing gum composition of claim 1 wherein said medium chain triglyceride is present in amounts of about 0.1% to about 40% by weight of said mixture.

18. The chewing gum composition of claim 1 wherein said gum base is selected from the group consisting of synthetic or natural elastomers.

19. The chewing gum composition of claim 1 wherein said delivery system further includes a saccharide-based material and formed by flash flow processing.

20. The chewing gum composition of claim 19 wherein said flash flow process is a flash heat or a flash shear process.

21. The chewing gum composition of claim 20 wherein the conditions of said flash heat process are provided by a spinning head.

22. The chewing gum composition of claim 1 wherein said particulate flavor delivery system is suspended in a solid fat having an intraparticle flow temperature lower than the melting point of said non-fat solid substrate.



23. The chewing gum composition of claim 22 wherein said particulate flavor delivery system suspended in a solid fat is formed by subjecting said composition to conditions of flash heat and disruptive force sufficient to form and maintain discrete solloids.

24. The chewing gum composition of claim 20 wherein said flash shear comprises the steps of subjecting said delivery system in an extruder to conditions of temperature and force sufficient to cause intraparticle flow of said fat but insufficient to melt said non-fat solid substrate and expelling said delivery system in a flowable state while applying a disruptive force to said composition to form discrete solloids.

25. The chewing gum composition of claim 1 further comprising a material selected from the group consisting of sweeteners, food acids, coloring agents, bulking agents, fillers, softeners, plasticizers and mixtures thereof.

26. A confectionery composition comprising:

- (i) a saccharide-based matrix; and
- (ii) a highly odorous flavor component delivery system comprising a non-fat solid substrate having imbibed therein or coated thereon a mixture of a highly odorous flavor oil component and a medium chain triglyceride.

27. The confectionery composition of claim 26 wherein the medium chain triglyceride has from 6 to 12 carbon atoms in the fatty acid chain.

28. The confectionery composition of claim 27 wherein the medium chain triglyceride is formed from a fatty acid selected from the group consisting of caprylic acid, apric acid, linoleic acid, caproic acid, lauric acid, succinic acid and mixtures thereof.

29. The confectionery composition of claim 27 wherein the highly odorous flavor component has a vapor pressure of at least about 40 mm at a temperature of about 160°C or less.

30. The confectionery composition of claim 29 wherein the highly odorous flavor oil component is selected from the group consisting of methyl acetate, ethyl acetate, 1-hexanol, benzaldehyde, benzyl alcohol, 1-octanol, 2-octanol, cinnamaldehyde, cinnamyl alcohol, naphthalene, p-cymene, thymol, camphene, d-limonene, myrcene,  $\alpha$ -pinene,  $\beta$ -pinene, terpenoline, camphor, 1-dihydrocarvone,  $\alpha$ -citral, d-fenchone, pulegone,  $\alpha$ -thujone, d-citronellal, cineol, dihydrocarveal, d,l-fenchyl alcohol, geraniol, d-linalool,  $\alpha$ -terpineol, 1-menthol, d-bornyl acetate, goranyl acetate, linalyl acetate, and mixtures thereof.

31. The confectionery composition of claim 27 wherein said flavor delivery system further comprises a flavor oil selected from the group consisting of peppermint oil, spearmint oil, eucalyptus oil, cinnamon oil, menthol oil of wintergreen (methylsalicylate), citrus oils, fruit essences and mixtures thereof.

32. The confectionery composition of claim 26 wherein said non-fat solid substrate is selected from the group consisting of cellulose, silicas, microcrystalline waxes, water-swellaable gums, water-swellaable mucilages, alginates, carageenans, tragacanth, starches, titanium dioxide, calcium carbonate, magnesium carbonate, zein and mixtures thereof.

33. The confectionery composition of claim 26 wherein said flavor delivery system is present in amounts of about 0.05% to about 30% by weight of the confectionery gum composition.

34. The confectionery composition of claim 26 wherein said medium chain triglyceride is present in amounts of about 0.1% to about 20% by weight of said mixture.

35. The confectionery composition of claim 26 wherein said non-fat solid substrate is present in said delivery system in amounts of about 0.1% to about 40% by weight.

36. The confectionery composition of claim 26 wherein said highly odorous flavor oil component is present in amounts of about 0.5% to about 30% by weight of said mixture.

37. The confectionery composition of claim 26 wherein said flavor component delivery system is formed by flash flow processing.

38. The confectionery composition of claim 37 wherein said flash flow process is a flash heat or flash shear process.

39. A comestible composition formed by the process comprising:

(i) providing a mixture of a non-fat solid substrate having imbibed therein or coated thereon a blend of a highly odorous flavor oil component and a medium chain triglyceride imbibed.

(ii) subjecting said mixture to conditions of temperature and force sufficient to induce flash flow of said substrate, whereby a solid matrix entrapping said highly odorous flavor oil component is formed.

40. A method of producing a high impact solid flavor delivery system comprising subjecting a mixture of a particulate non-fat solid substrate, a highly odorous flavor oil component and a medium chain triglyceride to conditions of temperature and force sufficient to induce flash flow.

41. A delivery system for highly odorous flavor oils comprising a non-fat solid substrate having imbibed therein in or coated thereon a mixture of a highly odorous flavor oil and a medium chain triglyceride.

42. A solid delivery system formed by the process of:

(a) providing a mixture of a non-fat solid substrate having imbibed therein or coated thereon a blend of a highly odorous flavor oil and a medium chain triglyceride; and

(b) subjecting said mixture to conditions of temperature and force sufficient to induce flash flow of said substrate, whereby a solid matrix entrapping said highly odorous flavor oil is formed.

43. A solid delivery system for highly volatile flavor oils comprising:

a stabilized, substantially non-volatile mixture comprising a highly volatile flavor oil and a medium chain triglyceride united with a flash-flow-formed matrix.

44. The solid delivery system of claim 43 wherein said medium chain triglyceride is selected from the group consisting of mono-, di- and polyhydric esters of a fatty acid and mixtures thereof.

45. The solid delivery system of claim 43 wherein said medium chain triglyceride has from 6 to 12 carbon atoms in the fatty acid chain.

46. The solid delivery system of claim 43 wherein the medium chain triglyceride is formed from a fatty acid selected from the group consisting of caprylic acid, capric acid, linoleic acid, caproic acid, lauric acid, succinic acid and mixtures thereof.

5

47. The solid delivery system of claim 46 wherein the medium chain triglyceride is the glycerol ester of said acids.

48. The solid delivery system of claim 43 wherein the highly odorous flavor oil component has a vapor pressure of at least about 40 mm at a temperature of about 160°C or less.

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US95/09903

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A23L 1/226; A32G 3/30

US CL : 426/3; 426/651

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 426/3, 4, 5, 6, 96, 650, 651

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS

search terms: flash flow, melt spin?, delivery system, flavor?, mct, medium chain triglyceride

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 3,095,258 (SCOTT) 25 June 1963.	1-48
A	US, A, 3,557,717 (CHIVERS) 26 January 1971.	1-48
A	US, A, 4,855,326 (FUISZ) 08 August 1989.	1-48
A	US, A, 5,236,734 (FUISZ) 17 August 1993.	1-48

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

Special categories of cited documents:	
*A* document defining the general state of the art which is not considered to be of particular relevance	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*1* earlier document published on or after the international filing date	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*1* document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*0* document referring to an oral disclosure, use, exhibition or other means	
*1* document published prior to the international filing date but later than the priority date claimed	*A* document member of the same patent family

Date of the actual completion of the international search

18 OCTOBER 1995

Date of mailing of the international search report

28 NOV 1995

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Rm PCT

Authorized officer

*Robert Thomas*

